



APPLICATIONS

The EM BoxPC is the perfect Plug&Play system solution, specially designed for FANLESS applications.

Typical application areas include:

- ▶ Industrial Control and Automation
- ▶ Measurement and Control
- ▶ Medical
- ▶ Infotainment
- ▶ Remote Management
- ▶ Extended Industrial Router

BoxPC-38



BoxPC-38

FEATURES

- ▶ Powered by the newest Intel® Atom™ processor E38xx Series (single, dual or quad core) up to 1.91 GHz
- ▶ Allows simultaneous use of UMTS and WLAN for extended router applications
- ▶ Wide range DC power input
- ▶ Supports up to 8GB DDR3L Memory
- ▶ Design, Production and Support "Made in Germany"

BENEFITS

- ▶ Low emission, high immunity
- ▶ Long term availability
- ▶ Free of rotating parts
- ▶ Full software compatibility
- ▶ Rugged & reliable choice for demanding embedded applications
- ▶ Small installation depth
- ▶ Integration-, application- and training-services available





BoxPC-38

EM BoxPC

OVERVIEW

The EM BoxPC is powered by latest technology including Intel® Atom™ Processors E38xx Series. An optional wireless module supporting GPRS, EDGE, UMTS and HSPA is available and at the same time a optional WiFi module can be used.

SPECIFICATION SUMMARY

- ▶ Fanless operation
- ▶ Gigabit Ethernet Port
- ▶ SATA Interfacing
- ▶ Modem solution with SIM card reader

SPECIFICATIONS

CPU

Single Core Intel® Atom™ processor
E3815/ 1.46 GHz/ 512 KB cache/ TDP 5W
Quad Cores Intel® Atom™ processor
E3845/ 1.91 GHz/ 2 MB cache/ TDP 10W
Dual Cores version on request

MAX. MEMORY

Up to 8GB DDR3L memory

BIOS

UEFI-BIOS

GBIT ETHERNET

Intel® WGI210IT Gigabit Ethernet controller
2x RJ45 on front side

MASS STORAGE SUPPORT

1x mSATA
1x on-board SATA connector

USB HOST PORTS

1x USB 3.0 Host Port Type A
4x USB 2.0 Host Ports Type A

SERIAL PORT

1x 9-pin male D-Sub connector for RS232

VIDEO INTERFACES

1x DVI-I connector (DVI and VGA)

MINI PCI EXPRESS SOCKET

1x PCIe with SIM card socket for wireless modem funktion
1x autodetect PCIe or mSATA

ADDITIONAL OPTIONS

1x High Definition Audio connectors
1x Headphone connector
Right side connectors:
1x RJ45, 1x CAN and 1x 9-pin male D-Sub for RS485 | Standard in Quad Core version
Additional front side connectors:
2x 9-pin male D-Sub
Possible combinations: CAN + RS485 or RS232 + RS485 or CAN + RS232

FANLESS

Designed for fanless operation

OS SUPPORT

Microsoft Windows® 7, 10
Microsoft Windows® 8, 8.1 on request
Linux on request

MANAGEMENT

Hardware monitoring

POWER INPUT

DC: 8V (min) to 32V (max) | with screw mounted 3-pin base strip plug (Phoenix Contact)
AC: Wide range option on request
100V to 240V | 50/60Hz

EMI SHIELDING

CE
EN55022:2006+A1204 / EN61000-6-2:2005
CLASS: A+B
Other upon request

SIZE

DC variant: Approximately (L x W x H)
235 mm x 150 mm x 44 mm
1U Rackmount Height

AC variant: Approximately (L x W x H)
235 mm x 230 mm x 44 mm
1U Rackmount Height

MOUNTING

Stand alone
Optional: DIN Rail mounting, 19" 1U rackmount kit
Other upon request

TEMPERATURE RANGE

Commercial temperature version
Operation: 0°C to +60°C ambient
Storage: -20°C to +85°C ambient

Industrial temperature version (option)
Operation: -40°C to +85°C ambient
Storage: -40°C to +85°C ambient

HUMIDITY

Maximum relative humidity of atmosphere
95%@40°C, non-condensing



EMTrust GmbH
Headquarters
Gewerbering 1
85258 Weichs - Germany
Phone +49 8136 80 677-800
Fax +49 8136 80 677-809
sales@emtrust.de
www.emtrust.de

Trucomp, Inc.
11555 Heron Bay Blvd
Suite 200
Coral Springs, FL 33076 - USA
Phone +1 954 603-0582
Fax +1 954 603-0581
sales@trucompusa.com
www.trucompusa.com

The information contained in this document has been carefully checked and is believed to be reliable. However, EMTrust GmbH makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of what ever nature resulting from the use of, or reliance upon, it. EMTrust does not guarantee that the use of any information contained herein will not infringe upon the patent, trademark, copyright or other rights of third parties, and no patent or other license is implied hereby. Intel and Intel logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

This document does not in any way extend EMTrust's warranty on any product beyond that set forth in its standard terms and conditions of sale. EMTrust reserves the right to make changes in the products or specifications, or both, presented in this publication at any time and without notice.

LIFE SUPPORT APPLICATIONS

EMTrust's products are not intended for use as critical components in life support appliances, devices or systems in which the failure of a EMTrust product to perform could be expected to result in personal injury. All mentioned trademarks are registered trademarks of their owner.

© 2015 EMTrust GmbH. All rights reserved. Rev. 1.0 / 08.06.2015