



APPLICATIONS

Featuring a nominal input voltage of 16.8V to 36V DC and four stabilised outputs, EMTrust's 3U, 12TE CompactPCI power supply units are fully compliant with the latest CompactPCI specifications and are compatible with the EMTrust PSU for mobile or rugged applications.

- ▶ Rugged Embedded Systems
- ▶ Instrumentation
- ▶ Robotics
- ▶ Industrial Control and Automation
- ▶ Maintenance-Free Systems
- ▶ Traffic and Transportation
- ▶ Measurement & Control

ICP-PSU-DC60

60W Modular DC/DC Power Supply Unit




ICP-PSU-DC60

FEATURES

- ▶ Dedicated CompactPCI PSU
- ▶ 60W continuous load output
- ▶ Fully protected stabilized outputs
- ▶ Automatic failure recovery
- ▶ EMI filtered
- ▶ Full safety compliance
- ▶ LED status and power indication

BENEFITS

- ▶ Open standard architecture
- ▶ Service & user friendly
- ▶ 19" cassette for improved maintenance
- ▶ Long-term product availability





ICP-PSU-DC60

PSU

OVERVIEW

All outputs are individually protected against overload, short circuits and over temperature conditions, and are capable of automatic recovery once the fault condition is rectified.

The PSU is designed for compliance with EN60950 safety standards, and can deliver up to 70W output at environmental temperatures up to 50°C.

SPECIFICATION SUMMARY

- ▶ 4 regulated DC outputs
- ▶ Fully protected
- ▶ Passive cooling
- ▶ Status LEDs
- ▶ Extended operational temperature
- ▶ High MTBF
- ▶ Rugged 3U cPCI format

SPECIFICATIONS

INPUT VOLTAGES	24V DC (nom.); 16.8V to 36V
FUSE	2.5AT (external)
OUTPUT	<ul style="list-style-type: none"> ▶ Ua1 +3.3V, 1%, 5A ▶ Ua2 +5.1V, 1%, 7A (10A max.) ▶ Ua3 +12V, 5%, 1A ▶ Ua4 -12V, 5%, 0.25A
TURN-ON	< 500ms
PROTECTION	Continuous short-circuit protection with auto recovery
COMPATIBILITY	Compatible with EMTrust UPS
POWER	60W @ +50°C (passive cooling)

EFFICIENCY	80% (typ.) at max. load
CONNECTORS	DIN EN 60603 (DIN 41612) M-connector
DERATING	36W @ +70°C; 18W @ +85°C
STATUS LEDs	+3.3V, +5.0V, +/-12.0V (yellow)
MASS	750g
OPERATING TEMP	0°C to +70°C
EXTENDED TEMP	-40°C to +85°C (derating > 50°C)
STORAGE TEMP	-40°C to +85°C

CLIMATIC CLASS	EN60654-1 Class B2
HUMIDITY	5% to 95% @ 40°C (non-condensing)
SAFETY	<ul style="list-style-type: none"> ▶ EN60950 ▶ Protection Class I ▶ Overvoltage Category II ▶ Pollution Degree 2
EMISSION	EN55022 Limit A
IMMUNITY	<ul style="list-style-type: none"> ▶ EN 61000-6-2 ▶ EN 61000-4-2 ▶ EN 61000-4-4 ▶ EN 61000-4-5 ▶ EN 61000-4-11
RAILWAY	EN 50155

ORDERING INFORMATION

PRODUCT	DESCRIPTION
ICP-PSU-DC60-t	24V DC/DC, switched-mode PSU with M power connector. The DC/DC PSU meets EN50155 for mobile applications.
KEY:	t- Temp. Range 0 = 0°C to +70°C 1 = -40°C to +85°C



EMTrust GmbH
Headquarters
 Gewerbering 1
 85258 Weichs - Germany
 Phone +49 8136 80 677-800
 Fax +49 8136 80 677-809
 sales@emtrust.de
 www.emtrust.de

Trucomp, Inc.
 11555 Heron Bay Blvd
 Suite 200
 Coral Springs, FL 33076 - USA
 Phone +1 954 603-0582
 Fax +1 954 603-0581
 sales@trucompusa.com
 www.trucompusa.com

The information contained in this document has been carefully checked and is believed to be reliable. However, EMTrust GmbH makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of what ever nature resulting from the use of, or reliance upon, it. EMTrust does not guarantee that the use of any information contained herein will not infringe upon the patent, trademark, copyright or other rights of third parties, and no patent or other license is implied hereby. Intel and Intel logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.
 This document does not in any way extend EMTrust's warranty on any product beyond that set forth in its standard terms and conditions of sale. EMTrust reserves the right to make changes in the products or specifications, or both, presented in this publication at any time and without notice.
 LIFE SUPPORT APPLICATIONS
 EMTrust's products are not intended for use as critical components in life support appliances, devices or systems in which the failure of a EMTrust product to perform could be expected to result in personal injury. All mentioned trademarks are registered trademarks of their owner.
 © 2013 EMTrust GmbH. All rights reserved. Rev. 1.6 / 21.11.2013